



INTRODUCING THE NEW HTS-580 SERIES TOTAL STATION



New Panel and LCD Design




New on-board Road Program




100,000 points internal memory capacity



External memory card slot



Data sharing possibilities using external memory card



Versatile methods of data transfer

NEW FEATURES

1. Wider LCD panel and redesigned keyboard Bright LCD backlight for clear and easy viewing. New Ergonomic buttons for comfortable and easy operation.

2. On board Road Design program which facilitates the design, customisation and construction of roads.

3. Upgraded Internal memory capacity of 100, 000 points ensures you never run out of memory space.

Using a standard 512k SD Card, the user can store up to another 100,000 data points.

4. Built in external memory support using SD card interface. The instrument can now store and transfer data conveniently to appropriate communication devices via a built-in SD memory card slot.

Survey data can now be transferred easily to PCs and Lap Tops for processing, Mobile phones for sending to another party, or another Total Station.

5. Users can now choose to transfer data to and from the total station using an external memory card, RS-232 or USB cable interface.

Bluetooth integration is also available to users as an option.

This means that the data transfer process is now much more versatile and convenient for the user, with so many data transfer options available.

HORIZON®
MEASURE RIGHT

SINGAPORE
SURVEY INSTRUMENTS SERVICES PTE LTD
50 Playfair Road, #08-01 Noel Building
Singapore 367995
Tel : (65) 6288 4622
Fax : (65) 6288 2033
www.horizon.sg
Email : info@horizon.sg

MALAYSIA
SURMAP SDN. BHD.
No. 81 Jalan SS15/4B,
47500 Subang Jaya,
Selangor Darul Ehsan, MALAYSIA
Tel: +603-5633 8877
Fax: +603-5880 9960
Email: surmap33@yahoo.com

CHINA
SIS SHANGHAI
Room 10C 32 10th Floor
Shanghaimart
2299 Yan An Road (West)
Shanghai 200336
Tel : +86-21-6236 0569
Fax : +86-21-6236 0614
Email : tang@horizon.sg

EUROPE
HORIZON INSTRUMENTS B.V
Boxmeerseweg 2D
5835 AC Beugen, The Netherlands
Tel : +31 485 361 053
Fax : +31 485 361 054
Email : info@surveying.nl
www.surveying.nl

USA
HORIZON MEASUREMENTS INC.
216 West 6th Street, Unit 101
San Bernardino,
California 92401 USA
Tel: +1-909-889-6020
Fax: +1-909-889-6080
Toll Free: 1-888-710-8282
Email: info@hmsurvey.com
www.hmsurvey.com

MIDDLE EAST
HORIZON SURVEY EQUIPMENT LLC
Office #1, Al Hashmi Building
28 Burj Nakeel, Deira DUBAI
United Arab Emirates
Tel : +971 4 2299512
Fax : +971 4 2299514
Email : Surveyeq@emirates.net.ae

HTS-580 SERIES SPECIFICATIONS

HTS-580 SERIES SPECIFICATIONS	HTS-582R	HTS-585R	HTS-582	HTS-585
Model	Reflectorless		Standard	
Laser Class	Class 3R Laser Product		NA	
Conformity	IEC 60852-1:2001		EN 60825-1:1994 +A1 1:1996	
Telescope	Fully Transiting, Coaxial Sighting & Distance Measuring Optics			
Image	Erect			
Magnification	30X			
Objective Aperture	45mm; EDM: 50mm			
Resolving Power	3"			
Field of view	1°30'			
Minimum Focus	1m			
Angle Measurement	Photoelectrical Scanning by Incremental Decoder			
Display Resolution	1"/ 5" Selectable			
Angle Accuracy (DIN 18723)	2"	5"	2"	5"
Measuring Mode	H: Clockwise/ Counterclockwise Selectable, 0 set, Angle Input, Availability. & V: Zenith 0/ Horizontal 0, selectable			
Measuring time	0.8s		1.8s	
Distance Measurement	Modulated laser type: 0.670 μ m Basic Frequency: 60MHz, Coaxial EDM		Infra-Red	
Laser Spot	7 x 14mm / 20m		NA	
Unit	Meters/ Feet Selectable			
Measuring Range				
a. Single Prism (64mm diameter)	5000m	3000m	2500m	2000m
b. Triple Prism (64mm diameter)	6000m	5000m	3000m	2500m
c. Mini prism (25.4mm diameter)	800m	800m	500m	500m
d. Retro Target	500m	300m	NA	NA
e. Reflectorless	120m/(200m)*	120m/(200m)*	NA	NA
Display Resolution	1mm			
Accuracy				
a. Fine mode with prism	2mm + 2ppm X D	2mm + 2ppm X D	2mm + 2ppm X D	2mm + 2ppm X D
b. Track mode with prism	3mm + 2ppm X D	5mm + 2ppm X D	2mm + 2ppm X D	5mm + 2ppm X D
c. Reflectorless mode	2mm + 2ppm X D	2mm + 2ppm X D	NA	NA
Measuring Time				
a. Fine mode with prism	1.4s	1.6s	1.8s	1.8s
b. Track mode with prism	1.2s	1.2s	0.7s	0.7s
c. Reflectorless mode	0.8s	0.8s	NA	NA
Metrological correction	Manual Input, Auto correction			
Atmospheric Refraction & Earth Curvature correction	Selectable K=0.14/ 0.02			
Sensitivity of vials	Plate Vial - 30" /2mm, Circular Vial - 8'			
Compensator				
System	Liquid Electric Detection type			
Compensator range	$\pm 3'$			
General				
Display Keyboard	Alphanumeric/ Dot matrix LCE/ White backlight/ on both faces/ 28 keys			
Data Storage	100, 000 points internal/ SD card compatibility external			
Data transfer interface	RS232/ USB selectable			
On board software	REM, MLM, Missing Line, Area, Point to Line, Layout, Offsets. Z-coordinates, Road Design			
Laser pointer	Yes		No	
Tribrach	3-pin forced groove, detachable			
Plummet	Optical plummet: Erect image, 3 x 0.3m to ∞ , Field View 5° Optional Integrated Laser plummet Class II product, Programmable on-board			
Battery	Compact Ni-H battery, 6V DC, Operation time 8 hrs			
Charger	Quick battery charger with separate power cord			
Operating temperature	-20°C to +50°C			
Size and Weight	200 x 180 x 350mm, 5.8kg			

* Measurement range of 200m is for the extended reflectorless models HTS-582RX and HTS-585RX